



Hybrid Inverter

SUN-5/6/8/10/12K-SG04LP3-EU/BE



- 100** 100% unbalanced output, each phase; Max. output up to **50%** rated power
-  DC couple and AC couple to retrofit existing solar system
- 10** Max. 10pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
- 240** Max. charging/discharging current of 240A
- 48** 48V low voltage battery, transformer isolation design
- 6** 6 time periods for battery charging/discharging
-  Support storing energy from diesel generator

Deye

Stock Code: 605117.SH

Model	SUN-5K -SG04LP3-EU/BE	SUN-6K -SG04LP3-EU/BE	SUN-8K -SG04LP3-EU/BE	SUN-10K -SG04LP3-EU/BE	SUN-12K -SG04LP3-EU/BE
Battery Input Data					
Battery Type	Lead-acid or Lithium-ion				
Battery Voltage Range (V)	40~60				
Max. Charging Current (A)	120	150	190	210	240
Max. Discharging Current (A)	120	150	190	210	240
External Temperature Sensor	Yes				
Charging Curve	3 Stages / Equalization				
Charging Strategy for Li-Ion Battery	Self-adaption to BMS				
PV String Input Data					
Max. DC Input Power (W)	6500	7800	10400	13000	15600
Rated PV Input Voltage (V)	550 (160~800)				
Start-up Voltage (V)	160				
MPPT Voltage Range (V)	200-650				
Full Load DC Voltage Range (V)	350-650				
PV Input Current (A)	13+13			26+13	
Max. PV I _{SC} (A)	17+17			34+17	
No.of MPP Trackers	2				
No.of Strings per MPP Tracker	1			2+1	
AC Output Data					
Rated AC Output Active Power (W)	5000	6000	8000	10000	12000
Max. AC Output Power (W)	5500/5000*1	6600/6000*1	8800/8000*1	11000/10000*1	13200/12000*1
Max. Output Apparent Power (VA)	5500/5000*2	6600/6000*2	8800/8000*2	11000/10000*2	13200/12000*2
AC Output Rated Current (A)	7.2	8.7	11.6	14.5	17.4
Max AC Output Current (A)	8	9.6	12.8	15.9	19.1
Max. Three-phase Unbalanced Output Current (A)	10.9	13	17.4	21.7	26.1
Max Output short circuit current (A)	75				
Max. Continuous AC Passthrough (A)	45				
Peak Power (off grid)	2 time of rated power, 10 S				
Power Factor	0.8 leading to 0.8 lagging				
Output Frequency and Voltage	50/60Hz; 3L/N/PE 220/380, 230/400Vac				
Grid Type	Three Phase				
Total Harmonic Distortion (THD)	<3% (of nominal power)				
DC current injection	<0.5% I _n				
Efficiency					
Max. Efficiency	97.60%				
Euro Efficiency	97.00%				
MPPT Efficiency	99.90%				
Protection					
Integrated	PV Input Lightning Protection, Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge protection				
Output Over Voltage Protection	DC Type II/AC Type III				
Certifications and Standards					
Grid Regulation	VDE4105, IEC61727/62116, VDE0126, AS4777.2, CEI 0 21, EN50549-1, G98, G99, C10-11, UNE217002, NBR16149/NBR16150				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
General Data					
Operating Temperature Range ()	-40~60°C, >45°C derating				
Cooling	Smart cooling				
Noise (dB)	≤45 dB				
Communication with BMS	RS485; CAN				
Weight (kg)	33.6				
Size (mm)	422W x 699.3H x 279D				
Protection Degree	IP65				
Installation Style	Wall-mounted				
Warranty	5 years				

1. For Belgium, Max. Output Power(W): SUN-5K-SG04LP3-BE is 5000; SUN-6K-SG04LP3-BE is 6000; SUN-8K-SG04LP3-BE is 8000; SUN-10K-SG04LP3-BE is 10000; SUN-12K-SG04LP3-BE is 12000.
 2. For Belgium, Max. Output Apparent Power (VA): SUN-5K-SG04LP3-BE is 5000; SUN-6K-SG04LP3-BE is 6000; SUN-8K-SG04LP3-BE is 8000; SUN-10K-SG04LP3-BE is 10000; SUN-12K-SG04LP3-BE is 12000.