Certificate of Conformity (COC)



Certificate Holder : NingBo Deye Inverter Technology Co., Ltd.

No. 26 South YongJiang Road, Daqi, Beilun, NingBo, China

Date of Original Issue : 2024-03-26

Date of Last Revision :

Date of Expiry : 2027-03-25 Certificate Number : PCS-24-1022

Product : Grid-connected PV Inverter

Ratings : See appendix on page 2 to page 4

Brand/Trademark :

Model

: SUN-3K-G06P3-EU-AM2, SUN-4K-G06P3-EU-AM2, SUN-5K-G06P3-EU-AM2,

SUN-6K-G06P3-EU-AM2, SUN-7K-G06P3-EU-AM2, SUN-8K-G06P3 -EU-AM2, SUN-9K-G06P3-EU-AM2, SUN-10K-G06P3-EU-AM2, SUN-12K-G06P3-EU-AM2, SUN-15K-G06P3-EU-AM2, SUN-3K-G06P3-EU-AM2-P1, SUN-4K-G06P3-EU-AM2-P1, SUN-5K-G06P3-EU-AM2-P1, SUN-6K-G06P3-EU-AM2-P1, SUN-7K-G06P3-EU-AM2-P1, SUN-8K-G06P3-EU-AM2-P1, SUN-9K-G06P3-EU-AM2-P1, SUN-10K-G06P3-EU-AM2-P1, SUN-9K-G06P3-EU-AM2-P1, SUN-10K-G06P3-EU-AM2-P1, SUN-9K-G06P3-EU-AM2-P1, SUN-10K-G06P3-EU-AM2-P1, SUN-9K-G06P3-EU-AM2-P1, SUN-10K-G06P3-EU-AM2-P1, SUN-1

SUN-12K-G06P3-EU-AM2-P1, SUN-15K-G06P3-EU-AM2-P1

Test Laboratory : SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

Testing Report : GZES220300424901, 2023-12-02, Amendment 01:2024-03-05

GZES220300424902, 2023-12-02, Amendment 01:2024-03-05

Test Standard : IEC 62116:2014 and IEC 61727:2004

This is to certify that the product has been tested and was found to comply with the requirements of the standard(s). The above-mentioned product is certified according to the requirements of ISO/IEC 17065:2012.

Christopher Hee Certification Officer

SGS Testing & Control Services Singapore Pte Ltd 30 Boon Lay Way #03-01 Singapore 609957





SGSGS CONTROL CONTROL



APPENDIX

Certificate Number: PCS-24-1022

Model	SUN-3K-G06P3- EU-AM2-P1	SUN-4K-G06P3- EU-AM2-P1	SUN-5K-G06P3- EU-AM2-P1	SUN-6K-G06P3- EU-AM2-P1	
Model (*)	SUN-3K-G06P3- EU-AM2	SUN-4K-G06P3- EU-AM2	SUN-5K-G06P3- EU-AM2	SUN-6K-G06P3- EU-AM2	
PV Input					
Recommended Max. PV input power (kW)	3.9	5.2	6.5	7.8	
Max. input voltage (V)		1100			
Start-up operating voltage (V)		140			
Rated input voltage (V)		600			
MPPT operating voltage range (V)		120-1000			
Full power MPPT voltage range (V)		350-850			
Max. input current (A)		20+20			
Max. short current (A)		30+30			
Max. input current (A) (*)	13+13				
Max. short current (A) (*)	19.5+19.5				
AC Output					
Nominal grid voltage (V)		3L/N/PE 230/400V			
Nominal grid frequency (Hz)		50/60			
Rated AC power (kW)	3	4	5	6	
Max. AC power (kW)	3.3	4.4	5.5	6.6	
Rated AC current (A)	4.4	5.8	7.3	8.7	
Max. AC current (A)	4.8	6.4	8.0	9.6	
Output power factor	0.8 leading~0.8 lagging				
General Data					
Operating temperature range		-25 ~ 60 °C,>45 °C derating			
Protection degree	COOK REAL PROPERTY AND ADDRESS OF THE PERSON NAMED IN COLUMN 1997 AND AD	IP65			
Protective class		Class I			
Cooling method	Free cooling				
Topology	CONSTRUCTION DESCRIPTION	Transformerless			

^(*) The difference between the model suffixes AM2 and AM2-P1 is the maximum input current and the maximum short-circuit current, refer to the above parameter table of detailed information.







APPENDIX

Certificate Number: PCS-24-1022 SUN-7K-G06P3-SUN-8K-G06P3-SUN-10K-G06P3-SUN-9K-G06P3-Model EU-AM2-P1 EU-AM2-P1 EU-AM2-P1 EU-AM2-P1 SUN-7K-G06P3-SUN-8K-G06P3-SUN-9K-G06P3-SUN-10K-G06P3-Model (*) EU-AM2 EU-AM2 EU-AM2 EU-AM2 PV Input Recommended Max. PV input power(kW) 9.1 10.4 11.7 13 Max. input voltage(V) 1100 Start-up operating voltage(V) 140 Rated input voltage(V) 600 MPPT operating voltage range(V) 120~1000 Full power MPPT voltage range (V) 480~850 Max. input current(A) 20+20 Max. short current(A) 30+30 Max. input current(A) (*) 13+13 Max. short current(A) (*) 19.5+19.5 AC Output 3L/N/PE 230/400V Nominal grid voltage(V) Nominal grid frequency (Hz) 50/60 Rated AC power(kW) 10 7 8 Max. AC power(kW) 7.7 8.8 9.9 11 Rated AC current(A) 10.2 11.6 13.1 14.5 Max. AC current(A) 11.2 12.8 14.4 16.0 Output power factor 0.8 leading~0.8 lagging General Data -25 ~ 60 °C,>45 °C derating Operating temperature range Protection degree **IP65** Protective class Class I Cooling method Free cooling Topology **Transformerless**





^(*) The difference between the model suffixes AM2 and AM2-P1 is the maximum input current and the maximum short-circuit current, refer to the above parameter table of detailed information.



APPENDIX

Certificate Number: PCS-24-1022

Model	SUN-12K-G06P3-EU-AM2-P1	SUN-15K-G06P3-EU-AM2-P1	
Model (*)	SUN-12K-G06P3-EU-AM2	SUN-15K-G06P3-EU-AM2	
PV Input	•		
Recommended Max. PV input power(kW)	15.6	19.5	
Max. input voltage(V)	1100		
Start-up operating voltage(V)	140		
Rated input voltage(V)	600		
MPPT operating voltage range(V)	120~1000		
Full power MPPT voltage range (V)	480~850		
Max. input current(A)	20+20	20+26	
Max. short current(A)	30+30	30+39	
Max. input current(A) (*)	13+13	13+26	
Max. short current(A) (*)	19.5+19.5	19.5+39	
AC Output			
Nominal grid voltage(V)	3L/N/PE 230/400V		
Nominal grid frequency (Hz)	50/60		
Rated AC power(kW)	12	15	
Max. AC power(kW)	13.2	16.5	
Rated AC current(A)	17.4	21.8	
Max. AC current(A)	19.2	24.0	
Output power factor	0.8 leading~0.8 lagging		
General Data			
Operating temperature range	-25 ~ 60 °C,>45 °C derating		
Protection degree	IP65		
Protective class	Class I		
Cooling method	Free cooling		
Topology	Transformerless		

^(*) The difference between the model suffixes AM2 and AM2-P1 is the maximum input current and the maximum short-circuit current, refer to the above parameter table of detailed information.



