

# Microinverter

SUN-D60/80/100/110G4-EU-Q0



- ✓ 1 MPP tracker, module level monitoring
- ✓ IP67 protection degree
- ✓ Wi-Fi communication and lora communication
- ✓ Rapid shutdown function
- ✓ Easy installation, suitable for quick-plug balcony PV system
- ✓ <100ms AC fast discharge, compliant with new required standard DIN VDE V 0126-95 (<200ms) to protect human safety
- ✓ Complete NS protection with self-check function
- ✓ 25 years design lifetime and 15 years warranty
- ✓ With integrate Wi-Fi
- ✓ Anti backflow function

**Deye**

Stock Code: 605117.SH

Model	SUN-D60G4-EU-Q0	SUN-D80G4-EU-Q0	SUN-D100G4-EU-Q0	SUN-D110G4-EU-Q0
<b>PV String Input Data</b>				
Max. PV Input Power (W)	210-420(2 Pieces)	210-560(2 Pieces)	210-700(2 Pieces)	210-770(2 Pieces)
Max. PV Input Voltage (V)	120			
Start-up Voltage (V)	20			
MPPT Voltage Range (V)	45-100			
Rated PV Input Voltage (V)	85			
Max. Operating PV Input Current (A)	18			
Max. Input Short Circuit Current (A)	27			
No. of MPP Trackers/ No. of Strings MPP Tracker	1/1			
<b>AC Output Side</b>				
Rated AC Output Active Power (W)	600	800	1000	1100
Max. AC Output Apparent Power (VA)	600	800	1000	1100
Rated AC Output Current (A)	2.8/2.7	3.7/3.5	4.6/4.4	5/4.8
Max. AC Output Current (A)	2.8/2.7	3.7/3.5	4.6/4.4	5/4.8
Rated Output Voltage/Range (V)	220/230 0.85Un-1.1Un			
Grid Connection Form	L/N/PE			
Rated Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65			
Power Factor Adjustment Range	0.9 leading-0.9 lagging			
Total Current Harmonic Distortion THDi	<3%			
DC Injection Current	<0.5%In			
Max. Unit per Branch	8	6	5	5
<b>Efficiency</b>				
Max. Efficiency	96.5%			
Euro Efficiency	96.0%			
MPPT Efficiency	>99%			
<b>Equipment Protection</b>				
DC Polarity Reverse Connection Protection	Yes			
AC Output Overcurrent Protection	Yes			
AC Output Overvoltage Protection	Yes			
AC Output Short Circuit Protection	Yes			
Thermal Protection	Yes			
DC Terminal Insulation Impedance Monitoring	Yes			
Power Network Monitoring	Yes			
Island Protection Monitoring	Yes			
Earth Fault Detection	Yes			
Overvoltage Load Drop Protection	Yes			
<b>General Data</b>				
Operating Temperature Range (°C)	-40 to +65°C, >45°C Derating			
Permissible Ambient Humidity	0-100%			
Permissible Altitude (m)	2000m			
Noise (dB)	≤25			
Ingress Protection(IP) Rating	IP 67			
Inverter Topology	Isolated			
Over Voltage Category	OVC II(DC), OVC III(AC)			
Communication	Wi-Fi			
Cabinet Size (WxHxD mm)	212×190×40 (Excluding Connectors and Brackets)			
Weight (kg)	2.7			
Warranty	15 Years			
Type of Cooling	Natural Cooling			
Grid Regulation	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, G99, VDE-AR-N 4105			
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2			