

Three Phase String Inverter

SUN-3/4/5/6/7/8/9/10/12/15K-G06P3-EU-BM2



2 MPP trackers, Max. efficiency up to 98.5%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)

Deye

Stock Code: 605117.SH

Model	SUN-3K-G06 P3-EU-BM2	SUN-4K-G06 P3-EU-BM2	SUN-5K-G06 P3-EU-BM2	SUN-6K-G06 P3-EU-BM2	SUN-7K-G06 P3-EU-BM2	SUN-8K-G06 P3-EU-BM2	SUN-9K-G06 P3-EU-BM2	SUN-10K-G06 P3-EU-BM2	SUN-12K-G06 P3-EU-BM2	SUN-15K-G06 P3-EU-BM2
PV String Input Data										
Max. PV Input Power (kW)	4.5	6	7.5	9	10.5	12	13.5	15	18	22.5
Max. PV Input Voltage (V)	1100									
Start-up Voltage (V)	140									
MPPT Voltage Range (V)	120-1000									
Rated PV Input Voltage (V)	600									
Max. Operating PV Input Current (A)	13+13									13+26
Max. Input Short Circuit Current (A)	19.5+19.5									19.5+39
No. of MPP Trackers/ No. of Strings MPP Tracker	2/1+1									2/1+2
AC Output Side										
Rated AC Output Active Power (kW)	3	4	5	6	7	8	9	10	12	15
Max. AC Output Apparent Power (kVA)	3.3	4.4	5.5	6.6	7.7	8.8	9.9	11	13.2	16.5
Rated AC Output Current (A)	4.6/4.4	6.1/5.8	7.6/7.3	9.1/8.7	10.7/10.2	12.2/11.6	13.7/13.1	15.2/14.5	18.2/17.4	22.8/21.8
Max. AC Output Current (A)	5/4.8	6.7/6.4	8.4/8	10/9.6	11.7/11.2	13.4/12.8	15/14.4	16.7/16	20/19.2	25/24
Rated Output Voltage/Range (V)	220/380V, 230/400V 0.85Un-1.1Un									
Grid Connection Form	3L/N/PE									
Rated Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65									
Power Factor Adjustment Range	0.8 leading to 0.8 lagging									
Total Current Harmonic Distortion THDi	<3%									
DC Injection Current	<0.5%In									
Efficiency										
Max. Efficiency	98.1%		98.2%			98.3%			98.5%	
Euro Efficiency	97.5%		97.6%			97.8%			98%	
MPPT Efficiency	>99%									
Equipment Protection										
DC Reverse Polarity Protection	Yes									
AC Output Overcurrent Protection	Yes									
AC Output Overvoltage Protection	Yes									
AC Output Short Circuit Protection	Yes									
Thermal Protection	Yes									
Insulation Impedance Detection	Yes									
DC Component Monitoring	Yes									
Arc Fault Circuit Interrupter (AFCI)	Optional									
Anti-islanding Protection	Yes									
Residual Current Detection	Yes									
Surge Protection Level	TYPE II(DC), TYPE II(AC)									
DC Switch	Yes									
Interface										
Communication Interface	RS485/RS232									
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)									
General Data										
Operating Temperature Range (°C)	-25 to +60°C, >45°C Derating									
Permissible Ambient Humidity	0-100%									
Permissible Altitude (m)	4000m									
Noise (dB)	<45									
Ingress Protection(IP) Rating	IP 65									
Inverter Topology	Non-Isolated									
Over Voltage Category	OVC II(DC), OVC III(AC)									
Cabinet Size (WxHxD mm) (Excluding Connectors and Brackets)	283×525×178									283×525×188
Weight (kg)	11.5									12
Warranty	5 Years									
Type of Cooling	Natural Cooling									
Grid Regulation	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, OVE-Richtlinie R25, G98, G99, VDE-AR-N 4105									
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2									