

Page: 0001



## CERTIFICATE OF SUITABILITY

Authorised marking: TUV-027029-E

TÜV Rheinland Australia Pty Ltd "Electrical Product Safety Certification (EPSC) Scheme", accredited by JAS-ANZ in accordance with ISO/IEC 17065, has issued this certificate under JAS-ANZ accreditation. The electrical equipment described hereunder has been evaluated and found to be electrically safe at the time of certification and met the minimum safety requirements contained in Australian Standard AS/NZS 3820 as of current. It is a requirement that all equipment supplied under this certificate shall be identical to the equipment as certified. The certificate holder may affix the above mentioned authorised marking on the product.

**CERTIFICATE HOLDER:** NingBo Deye Inverter Technology

Co., Ltd.

No. 26 South YongJiang Road, Daqi,

Beilun NingBo, 315800 Zhejiang P.R. China

**DESCRIPTION OF EQUIPMENT** 

**Declared class:** Non-declared

Hybrid Inverter Product:

Trade Name / Manufacturer: DEYE

**Model Number:** 1) SUN-12K-SG01LP1-AU-AM3, 2) SUN-14K-SG01LP1-AU-AM3

3) SUN-16K-SG01LP1-AU-AM3

Ratings refer to CONTINUATION SHEET 1-2 for details Ratings:

AS/NZS 4777.2:2020+A1 Standard:

> IEC 62109-1:2010 IEC 62109-2:2011

**Issue Date:** 05/04/2023 05/04/2028 **Expiry Date:** 

Signed for and on behalf of TÜV Rheinland Australia Pty Ltd

JAS-ANZ

www.ias-anz.org\register

Grant Li

TUV Rheinland Australia Pty Ltd 182 Dougharty Road, Heidelberg West VIC 3081

Phone: +61 (3) 9450 1400 Email: certification@au.tuv.com Website: www.au.tuv.com

Certificate Number:

AZ 69027029

Page: 0002



## **CERTIFICATE OF SUITABILITY**

Authorised marking:

TUV-027029-E

**CONTINUATION SHEET 1** 

Description of Equipment

Ratings:

For all models:

Protection: Class I, IP65, PD2 (Inside), PD3 (Outside) Operating Temp.: -40°C to 60°C (>45°C derating), Overvoltage Category (OVC): DC input: II; AC Output: III

PV input:

VDC max: 500 Vd.c.,

VDC MPPT: 150 – 425 Vd.c., IDC max: 26+26+26A, Isc PV: 44+44+44A

Battery input:

maximum voltage: 60Vdc

Battery voltage range: 40 – 60Vdc

Max charging / discharging current: 1) 220A, 2) 250A, 3) 290A

Battery type: Lead-acid or Li-ion

Issue Date: 05/04/2023 Expiry Date: 05/04/2028

Signed for and on behalf of TÜV Rheinland Australia Pty Ltd

JAS-ANZ

www.jas-anz.org\register

Grant Li

TUV Rheinland Australia Pty Ltd 182 Dougharty Road, Heidelberg West VIC 3081 Phone: +61 (3) 9450 1400

Phone: +61 (3) 9450 1400
Email: certification@au.tuv.com
Website: www.au.tuv.com

Certificate Number:

AZ 69027029

Page: 0003



## **CERTIFICATE OF SUITABILITY**

Authorised marking:

TUV-027029-E

**CONTINUATION SHEET 2** 

Description of Equipment

Output:

Output voltage: 230/240V, L/N/PE Output frequency: 50/60Hz,

Rated Output Power: 1) 12kW, 2) 14kW, 3) 16kW

Max / Rated Output Apparent Power: 1) 12kVA, 2) 14kVA, 3) 16kVA

Max / Rated output current: 1) 52.2A, 2) 60.9A, 3) 69.6A

Power factor: 0.8 leading to 0.8 lagging,

GEN port:

Rated input voltage: 230/240V, L/N/PE

Rated input frequency: 50/60Hz,

Rated input Power: 1) 12kW, 2) 14kW, 3) 16kW Rated input current: 1) 52.2A, 2) 60.9A, 3) 69.6A

Issue Date: 05/04/2023

Expiry Date: 05/04/2028

Signed for and on behalf of TÜV Rheinland Australia Pty Ltd

Jane 1

JAS-ANZ

www.jas-anz.org/register

Grant Li

TUV Rheinland Australia Pty Ltd 182 Dougharty Road, Heidelberg West VIC 3081 Phone: +61 (3) 9450 1400 Email: certification@au.tuv.com

Website: www.au.tuv.com

0/020 h 04.08 ® TÜV, TUEV and TUV are registered trademarks. Utilisation and application requires prior appro