

Certificate of Conformity

By the product certificate number:

No. 230022RECO09-CER

Issued to:

License holder:

NingBo Deye Inverter Technology Co., Ltd.

No. 26 South YongJiang Road, Daqi, Beilun, NingBo, China

Trademark:

Manufacturer:

NingBo Deye Inverter Technology Co., Ltd.

No. 26 South YongJiang Road, Dagi, Beilun, NingBo, China

It is certified that the product:

Type of generating unit:

Hybrid inverter

Models:

SUN-29.9K-SG01HP3-EU-BM3, SUN-30K-SG01HP3-EU-BM3,

SUN-35K-SG01HP3-EU-BM3, SUN-40K-SG01HP3-EU-BM4, SUN-50K-SG01HP3-EU-BM4.

Technical Data:

Nominal power [W]

See page 2

Nominal voltage [V]

3/N/PE, 230/400 V

Nominal frequency [Hz]

50 Hz / 60 Hz

Firmware version

MAIN: Ver 3102

Number of phases

Three Phase

Isolation Transformer

No

Is in compliance with the standard:

IEC 62116: 2014. "Test procedure of islanding prevention measures for utility-interconnected photovoltaic inverters."

This certificate is based upon the test results of the Test Report GZES221102230702 (1) (1) The tests shown in this test report are carried out at a frequency of 50 Hz and 60 Hz.

The above-mentioned generating unit is certified according to the SGS internal procedure PE.T-ECPE-18 based on the requirements of the UNE-EN ISO / IEC 17065.

First issued on 16th May 2023 This certificate is valid until 16th May 2028

Madrid, 16th May 2023

for Product Certification at

Daniel Arranz Muñiz Certification Manager



SGS Tecnos, S.A.U. C/ Trespaderne, 29 - 28042 Madrid This certificate is issued by SGS under its General Conditions The status and validity of the certificate can be checked scanning the QR code above included or through the following web link. This document cannot be reproduced partially





No. 230022RECO09-CER Page 1 of 2



Full list of product references and nominal characteristics:

Model	SUN-29.9K- SG01HP3-EU- BM3	SUN-30K- SG01HP3-EU- BM3	SUN-35K- SG01HP3-EU- BM3	SUN-40K- SG01HP3-EU- BM4	SUN-50K- SG01HP3-EU- BM4
PV Input					L
Rated input voltage	600 V				
MPPT operating voltage range	150~850 V				
Max. input current	36/36/36 A			36/36/36 A	
Max. short current	55/55/55 A			55/55/55/55 A	
Battery Input					
Battery Type	Li-lon				
Battery Voltage Range	160~800 V				
Max. Charging Current	50/50 A				
Max. Discharging Current	50/50 A				
AC Output					
Rated AC power	29900 W	30000 W	35000 W	40000 W	50000 W
Max. AC power	29900 VA	33000 VA	38500 VA	44000 VA	55000 VA
Rated AC current	43.4 A	43.5 A	50.8 A	58.0 A	72.5 A
Max. AC current	43.4 A	47.9 A	55.8 A	63.8 A	79.8 A



