


Three Phase String Inverter(LV)

SUN-6/8K-G06P3-EU-CM2-LV-P1



127V/220V, 133V/230V and
50/60Hz, Three phase system



2 MPP trackers, Max. efficiency up to 98.3%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)

Deye

Stock Code: 605117.SH

Model	SUN-6K-G06P3-EU-CM2-LV-P1		SUN-8K-G06P3-EU-CM2-LV-P1	
PV String Input Data				
Max. PV Input Power (kW)	9		12	
Max. PV Input Voltage (V)			800	
Start-up Voltage (V)			250	
MPPT Voltage Range (V)			200-700	
Rated PV Input Voltage (V)			500	
Max. Operating PV Input Current (A)	20+20		20+26	
Max. Input Short Circuit Current (A)	30+30		30+39	
No. of MPP Trackers/ No. of Strings MPP Tracker	2/1+1		2/1+2	
AC Output Side				
Rated AC Output Active Power (kW)	6		8	
Max. AC Output Apparent Power (kVA)	6		8	
Rated AC Output Current (A)	15.8/15.1		21/20.1	
Max. AC Output Current (A)	15.8/15.1		21/20.1	
Rated Output Voltage/Range (V)	127V/220V , 133V/230V 0.85Un-1.1Un			
Grid Connection Form	3L/N/PE			
Rated Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65			
Power Factor Adjustment Range	0.8 leading to 0.8 lagging			
Total Current Harmonic Distortion THDi	<3%			
DC Injection Current	<0.5%In			
Efficiency				
Max. Efficiency			98.3%	
Euro Efficiency	97.8%		98.0%	
MPPT Efficiency			>99%	
Equipment Protection				
DC Reverse Polarity Protection	Yes			
AC Output Overcurrent Protection	Yes			
AC Output Overvoltage Protection	Yes			
AC Output Short Circuit Protection	Yes			
Thermal Protection	Yes			
Insulation Impedance Detection	Yes			
DC Component Monitoring	Yes			
Arc Fault Circuit Interrupter (AFCI)	Optional			
Anti-islanding Protection	Yes			
Residual Current Detection	Yes			
DC Switch	Yes			
Surge Protection Level	TYPE II(DC), TYPE II(AC)			
Interface				
Communication Interface	RS485/RS232 /WiFi/LAN			
LCD/LED Display	LCD1602			
General Data				
Operating Temperature Range (°C)	-25 to +60°C			
Permissible Ambient Humidity	0-100%			
Permissible Altitude (m)	4000m			
Noise (dB)	<45			
Ingress Protection(IP) Rating	IP 65			
Inverter Topology	Non-Isolated			
Over Voltage Category	OVC II(DC), OVC III(AC)			
Cabinet Size (W×H×D mm) (Excluding Connectors and Brackets)	283×525×178		283×525×188	
Weight (kg)	11.5		12	
Warranty	5 Years			
Type of Cooling	Natural Cooling			
Grid Regulation	NBR 16149,NBR 16150, EN 50549,RD 140			
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2			