





# Commissioning Steps of The Smart Devices

# 1.1 Instruction of installation


Step1: Unscrew the sealing cover of one COM inlet of the inverter, and fix the smart TX to this inlet.



Step2: Connect the meter port of the inverter and the RJ45 port of the smart TX using the communication cable from the accessory package.  
Step3(Optional): If the meter port of inverter can't output 5V DC power, please use the external USB to Type-C power cable to connect the Type-C port of Smart TX and the external power source.




## 1.2 LCD operation flow chart




Note: If the Smart Devices option is not available under System Setup on your hybrid inverter's LCD display, please contact your after-sales support team to upgrade the inverter's firmware. If your inverter's hardware version is too old, it may not be compatible with any firmware version that includes the Smart Devices feature—final eligibility must be confirmed by your after-sales support team.

### 1.3 System Setup Menu




Click on the "Smart Devices" item in the upper right corner of the "System Setup" page to enter the "Smart Devices" page.

### 1.4 Smart Devices Menu



There are four function options on the "Smart Devices" page: Smart CT, Smart Switch, Smart EV Charger, Smart TX.

#### 1.4.1 Smart CT



Click on "Smart CT" item in the upper left corner of "Smart Devices" page to enter the left page. On this page, you can enter up to 2 serial numbers of the smart CT meter and determine whether to enable them. The series number of Deye smart CT meter can be found on its nameplate.

Note: (1)CT1 corresponds to the wireless CT meter installed at the grid connection point, and CT2 corresponds to the wireless CT meter installed on the on-grid inverter side.  
(2)After enabling the Smart CT meter on the inverter LCD or APP, Please refer to the below steps to perform channel scanning to establish LoRa communication with the smart TX.



Click the link below to download the user manual of the smart CT: "[https://hqcndn.hqsmartcloud.com/deyeinverter/2025/09/19/%E3%80%90b%E3%80%91manual\\_sun-smart-ct01\\_30240301004\\_804\\_20250919\\_en-1.pdf](https://hqcndn.hqsmartcloud.com/deyeinverter/2025/09/19/%E3%80%90b%E3%80%91manual_sun-smart-ct01_30240301004_804_20250919_en-1.pdf)".

# Steps of "SN input"

Smart Devices

CT1:2024083109

☒ Enable

CT2:2024083110

☐ Enable

ESC

OK

SN Input

8990ABBEDD

Edit SN

CANCEL

SN Input

D25206020B

Edit SN

Editing a new SN may result in the loss of the old SN, please operate with caution

CANCEL

OK

SN Input

D25206020B

DEL

123456

7890AB

CDEF

CANCEL

OK

Step 1: After clicking the SN input text boxes beside CT1 and CT2 on the Smart CT page respectively, you can enter the "SN input" page.

Step 2: Click the "Edit SN" button and then click the "OK" button on the "SN input" page, the soft keyboard will appear on the screen so you can enter the SN serial number of the smart devices, which can be found on the label of the smart devices itself.

Step 3: After completing the input and confirming it is correct, click "OK" to save the setting.

# 1.4.2 Smart Switch

Smart Devices

Edit name

switch10

SN10:22222222

☐ Enable

☐ Time Mode

☐ Manual Mode

| Start-T | End-T | ON-SOC | OFF-SOC | ON/OFF                    |
|---------|-------|--------|---------|---------------------------|
| 01:00   | 09:00 | 50%    | 20%     | <input type="radio"/> OFF |
| 09:00   | 15:00 | 50%    | 20%     | <input type="radio"/> OFF |
| 15:00   | 23:00 | 50%    | 20%     | <input type="radio"/> OFF |
| 23:00   | 01:00 | 50%    | 20%     | <input type="radio"/> OFF |

☐ off grid-sw off

UPDOWN

ESCOK

Week

☒ Mon☒ Tue☒ Wed☒ Thu☒ Fri☒ Sat☒ Sun

Smart Devices

Edit name

switch10

SN10:22222222

☐ Enable

☐ Time Mode

☒ Manual Mode

| Start-T | End-T | ON-SOC | OFF-SOC | ON/OFF                    |
|---------|-------|--------|---------|---------------------------|
| 01:00   | 09:00 | 50%    | 20%     | <input type="radio"/> OFF |
| 09:00   | 15:00 | 50%    | 20%     | <input type="radio"/> OFF |
| 15:00   | 23:00 | 50%    | 20%     | <input type="radio"/> OFF |
| 23:00   | 01:00 | 50%    | 20%     | <input type="radio"/> OFF |

☐ off grid-sw off

UPDOWN

ESCOK

Week

☒ Mon☒ Tue☒ Wed☒ Thu☒ Fri☒ Sat☒ Sun

Click on "Smart Switch" item in the upper right corner of "Smart Devices" page to enter the left page. Under this function, you can add up to 10 smart Switch/Plug.

Click "UP" and "DOWN" buttons on the screen to jump to any smart switch/plug you want to set.

After checking the checkbox in front of "Enable" in the upper left corner of this page, you can follow the "SN input" steps to enter the series number of each Smart switch/plug and you can also customize the name of each switch/plug following steps of "Edit name".

**Note:** After adding smart switches/plugs to the inverter and ticked the 'Enable' option, please refer to the flowchart below (including in the user manual of the smart switch/plug) for channel scanning in order to establish LoRa communication with the smart TX.

**Time mode:** Use the programmable parameters on the zone 1 to control the ON/OFF status of smart switch/plug, and these programmable parameters

also have the corresponding settable options on the APP or website of the cloud platform. The 24 hours of a whole day will be divided into four time periods (Only the fourth time period can cross zero o'clock), and the ON/OFF status of the smart switch/plug can be controlled separately in each time period.

**Start-T:** The starting time point of each time period.

**End-T:** The end time point of each time period.

**ON-SOC:** Be valid only when the ON/OFF button of this time period is in ON status. When the battery SOC rises to this set value, this smart switch/plug will be turned on automatically.

**OFF-SOC:** Be valid only when the ON/OFF button of this time period is in ON status. When the battery SOC drops to this set value, this smart switch/plug will be turned off automatically.


**ON/OFF button:** In the OFF state, this smart switch/plug will always be turned off during the current time period. In the ON state, this smart switch/plug will be turned on/off automatically based on the judgment of ON-SOC and OFF-SOC.

**Week:** To choose which days of the week need to follow the above programmable schedule. If all options are not checked, it is equivalent to all options being checked.


**Manual mode:** Use the ON/OFF button on the zone 2 of the screen, the power button of the smart plug or the "SET" button of the smart switch, and the corresponding ON/OFF button on the APP and website of the cloud platform to control the ON/OFF status of this smart switch/plug manually. Remember that the manual mode and time mode can not be enabled in the same time.

**off grid-sw off:** After enabling, when the inverter switches from on-grid mode to off-grid mode, all smart switches/plugs connected to this inverter will be turned off automatically.

**Note:** Under Manual mode, after clicking the ON/OFF button in Area 2, you need to click the "OK" button at the middle of the far right side of the page to confirm and send the command to the smart switch/plug.



Click the link below to download the user manual of the smart plug : " [https://hqcndn.hqsmartcloud.com/deyeinverter/2025/09/19/%E3%80%90b%E3%80%91manual\\_sun-smart-plug01-f30240301004772\\_20250919\\_en-1.pdf](https://hqcndn.hqsmartcloud.com/deyeinverter/2025/09/19/%E3%80%90b%E3%80%91manual_sun-smart-plug01-f30240301004772_20250919_en-1.pdf) " .



Click the link below to download the user manual of the smart switch: " [https://hqcndn.hqsmartcloud.com/deyeinverter/2025/09/19/%E3%80%90b%E3%80%91manual\\_sun-smart-switch01p330240301004498\\_20250919\\_en-1.pdf](https://hqcndn.hqsmartcloud.com/deyeinverter/2025/09/19/%E3%80%90b%E3%80%91manual_sun-smart-switch01p330240301004498_20250919_en-1.pdf) " .

# Steps of "Edit Name"

Smart Devices

SN10:222222222

☒ Enable

☐ Time Mode

☐ Manual Mode

Start-T

End-T

ON-SOC

OFF-SOC

01:00

09:00

50%

20%

09:00

15:00

50%

20%

15:00

23:00

50%

20%

23:00

01:00

50%

20%

☐ OFF

☐ OFF

☐ OFF

☐ OFF

off grid-sw off

UP

DOWN

ESC

OK

Week

☒ Mon

☒ Tue

☒ Wed

☒ Thu

☒ Fri

☒ Sat

☒ Sun

SN Input

Switch1

Edit name

Editing a new SN may result in the loss of the old name, please operate with caution

CANCEL

OK

SN Input

switch1

DEL

a

b

c

d

e

f

g

h

i

j

k

l

m

n

o

p

q

f

s

t

u

v

w

x

y

z

CANCEL

OK

- Step 1: Click "UP" and "DOWN" buttons on the screen to jump to the smart switch/plug you want to set, and then enable this smart switch/plug.
- Step 2: Click the textbox in the upper right corner on the "Smart devices" page to enter the "SN input" page.
- Step 3: Click the "Edit name" button and then click the "OK" button on the "SN input" page, the soft keyboard will display on the screen for you to type in the desired name of this smart switch/plug.
- Step 4: After completing the input and confirming it is correct, click "OK" to save the setting.
- Note:** Arabic numerals and spaces cannot be entered. If you make a mistake, you have to delete all content and re-enter it. For better name editing, it is recommended to operate through the cloud platform APP. However, the name of the smart switch/plug on the LCD screen will not be automatically synchronized with the APP.

### 1.4.3 EV charger

Smart Devices

SN 2024103294

☒

☐ Plug and play

☒ Free work

☐ Time of charge

| Start-Time | End-Time | Charge                              |                                                                   |
|------------|----------|-------------------------------------|-------------------------------------------------------------------|
| 05:30      | 06:10    | <input checked="" type="checkbox"/> | <input type="checkbox"/> Solar energy only (SOC>95%)              |
| 08:10      | 20:35    | <input checked="" type="checkbox"/> | <input type="checkbox"/> Off grid EV Charge off >20% Off grid SOC |
| 20:35      | 22:35    | <input type="checkbox"/>            | <input type="checkbox"/> EV_Charge device connect at Grid port    |
| 22:35      | 05:30    | <input checked="" type="checkbox"/> | <input type="checkbox"/> EV_Charge device connect at LD port      |

3000W

Max charge power

ESC

OK

Click on "Smart EV charge" item in the down left corner of "Smart Devices" page to enter the left page. After checking the CheckBox in the upper left corner of this page, you can follow the previous "SN Input" steps to enter the series number of this EV charger which can be found on its label.

**Note:** The steps to add an EV charger can also be completed through the APP. Please refer to the user manual of EV charger for specific instructions. After adding the EV

**charger, please refer to the instructions in the user manual of EV charger to perform channel scanning in order to establish LoRa communication with the smart TX.**

**Plug and play:** The EV charger will operate like a common load, without the need to follow programmable schedule settings.

**Time of charge:** Control the use of EV charger according to the programmable schedule. 24 hours a day will be divided into four time periods (only the fourth period can pass midnight), and whether to use the EV charger to charge the electric vehicle during each time period can be controlled separately.

**Solar energy only(SOC>95%):** When the battery SOC is less than 99%, the charging power limit sent by the inverter to the EV charger will be 0. Only when the battery SOC is greater than or equal to 99% will the inverter output a non-zero charging power limit, allowing the charger to start charging. Once the battery SOC drops to  $\leq 95\%$ , the charging power limit sent by the inverter will return to 0, and the charger will stop charging.

In this mode, "Solar sell" under "System work mode" must be enabled simultaneously to ensure proper operation.

**Free work:** The AC power output from the inverter module (from solar power and battery discharging power) and the AC power input from the bypass circuit can both be used to power the EV charger.


**Off grid EV Charge off:** When the hybrid inverter switches to off-grid mode and the SOC of the battery isn't higher than the set value of "Off grid SOC", the EV charger will be automatically turned off.

**Off grid SOC:** When the hybrid inverter switches to off-grid mode, the EV charger will keep operating if the SOC of the battery is higher than this set value.

**EV\_charge device connect at Grid port:** The EV charger is connected on the Grid port side of the hybrid inverter.

**EV\_charge device connect at LD port:** The EV charger is connected on the Load port side of the hybrid inverter.

**Max charge power:** The maximum charging power allowed in both "Plug and play" mode and "Time of charge" mode.Range: 0-22000W. In LoRa control mode, the EV charger can only operate normally after receiving this value set by the hybrid inverter.



Press and hold the button for at least 1 second until the LED strip turns purple to enter channel scanning mode. After successful channel scan, the LoRa indicator blinks once per second.

Click the link below to download the user manual of the EV charger: "<https://deyeinverter.com/download/product-manual/?tag=54,57>".

## 1.4.4 Smart TX

Smart Devices

☐ Reset Smart TX  

Channel:3

ESC

OK

Click on "Smart TX" item in the down right corner of "Smart Devices" page to enter the left page.

**Reset Smart TX:** Restore factory settings, including restoring the communication channel to the factory default channel and clearing the bound sub device information.

Click the zone 1 and press the "UP" and "DOWN" button on the inverter's panel to change the communication channel (frequency) as you desired, this operation can also be conducted on the APP and website of the cloud platform.

**Kind reminder:** When adjusting the LoRa communication channel of a smart TX, all other smart devices that are communicating with it normally will automatically follow and adjust their own LoRa communication channels accordingly.

Advanced Function

☐ Parallel  
☒ Master  
☐ Slave

Modbus SN  
 01

☒ A Phase  
☐ B Phase  
☐ C Phase

☒ Ex\_Meter For CT  

☐ A Phase +  
☐ B Phase +  
☐ C Phase +

Meter Select  
 Smart-TX 6/7

☒ Disable Smart CT  
☐ Grid Tie Meter2

↑

↓

×

✓

If the Smart TX needs to communicate with the inverter, you should enable the "EX\_Meter For CT" function in the "Advanced Function" page on the inverter side, and also select the "Smart TX" option in the Meter Select setting.

## 2. Detail page of smart devices

02/25/2025 14:30:16 Fri

0 0.00 15 KW

0 0.00 15 KW

0 0.08 15 KW

0 0.02 15 KW

Smart Devices

CT1:2.14KW

EV:0.00KW

switch1 0.00KW TM-OFF

switch2 0.00KW ON

switch3 0.00KW ON

switch4 0.00KW

switch5 0.00KW

switch6 0.00KW OFF

switch7 0.00KW TM-OFF

3

Inverter

Power:-51W

50.0Hz

L1:222V

I1:0.8A

2

This is the detailed operational information page for smart devices.

When the LCD is on the inverter details page, pressing the UP and DOWN buttons on the inverter panel will turn the LCD to this page.

On the current page, you can see the working status of all smart CTs, EV charger, and smart switches/plugs connected to this inverter, smart switches/plugs in manual mode can be controlled the ON/OFF status through the ON/OFF button on the current page.

After manually operating the ON/OFF button beside the smart switch/plug, you also need to tap the "OK" button in the top right corner to send the command to the smart switch/plug devices.

## 3. Device info

Device Info.

0515 Smart TX: A25C200002 Flash

Ver: Ver C169

D25227028C/V0000

D25209023B/V0000

D252280206/V0000

D2561201FF/V0000

D2522702C5/V0000

D25608028C/V0000

D252270276/V0000

D256080280/V0000

D252090264/V0000

D252270395/V0000

Device Info

Up Arrow

Down Arrow

Close

Check

On the original Device Info page, click the up or down arrow buttons on the right side of the LCD screen to page through and view information such as the serial numbers and firmware versions of the four types of smart devices.

